

Page 1 of 6 BLGFK0038

# FITTING INSTRUCTIONS FITTING INSTRUCTIONS FOR BLGFK0038 BRAKE LEVER-GUARD FITTING KIT TRIUMPH TRIDENT 660 2021-



#### THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED OVER PAGE.

SOME PARTS MAY BE SHOWN FOR CLARITY OF INSTRUCTIONS ONLY.

DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

#### PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING.

## IF IN ANY DOUBT WHEN FITTING OUR PRODUCTS, CONSULT ONE OF OUR DEALERS OR HAVE FITTED BY A QUALIFIED TECHNICIAN.

PLEASE NOTE THAT THE WAY THE KIT IS PACKED DOES NOT NECESSARILY REPRESENT THE WAY OF MOUNTING TO THE BIKE.

IN THE EVENT OF RUBBER WASHERS BEING USED TO HOLD COMPONENTS ONTO BOLTS,

THESE RUBBER WASHERS CAN BE THROWN AWAY.

#### DIGITAL COPIES OF THESE INSTRUCTIONS ARE AVAILABLE FROM:

WWW.RG-RACING.COM

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 <a href="www.rg-racing.com">www.rg-racing.com</a> Email: <a href="mailto:info@rg-racing.com">info@rg-racing.com</a>




Page **2** of **6** BLGFK0038

TOOLS REQUIRED	GENERAL TORQUE SETTINGS
ALLEN KEY SET	M4 BOLT = 8Nm
	M5 BOLT = 12Nm
	M6 BOLT = 15Nm
	M8 BOLT = 20Nm
	M10 BOLT = 40Nm
	M12 BOLT = 40Nm

#### **LEGEND**

ITEM NO.	DESCRIPTION	QTY
ITEM 1	M6 x 1 x 35.00mm CAP-HEAD BOLT	1
ITEM 2	PLG0005COMP MOULDED LEVER GUARD	1
ITEM 3	M6x22mmØ FLAT WASHER	1
ITEM 4	M6x10mmØ FLAT WASHER	1
ITEM 5	NC0008 - M6 NUT CAP	1

## **EXPLODED ASSEMBLY VIEW**





Page **3** of **6** BLGFK0038

### FITTING INSTRUCTIONS

- To fit the Lever Guard (Item 2), remove the original bar end and store away safely.
- Insert the M6 cap head bolt (**Item 1**) through the M6 flat washer (**Item 4**), then through the Lever Guard (**Item 2**).
- Locate the larger 22mm washer (Item 3) through the protruding end of the bolt.
- Locate this assembly onto the bar & loosely tighten the bolt.
- Position so that when the motorcycle is at full lock in both directions it does not contact any other part of the motorcycle.
- Ensure that the assembled components match the exploded diagram shown on page 2.
- Fully tighten the bolt and check the operation of the throttle, steering & front brake lever before riding.

ISSUE 1 - 15/09/2021 (TB)

IMPORTANT - WHEN FITTING THIS PRODUCT, IT IS YOUR RESPONSIBILITY TO ENSURE THAT THE PRODUCT IN NO WAY IMPEDES THE OPERATION OF THE MOTORCYCLE AND IS CHECKED REGULARLY FOR TIGHTNESS AND CORRECT OPERATION.

#### FAILURE TO CHECK THE ABOVE COULD RESULT IN SERIOUS INJURY OR DAMAGE.

#### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



Page 4 of 6 BLGFK0038

#### NOTICE DE MONTAGE POUR BLGFK0038 KIT DE MONTAGE PROTÈGE LEVIER DE FREIN TRIUMPH TRIDENT 660 2021-



#### CE KIT CONTIENT LES ARTICLES ILLUSTRES ET ETIQUETES SUR LA PAGE.

CERTAINES PARTIES PEUVENT ETRE PRESENTES UNIQUEMENT POUR LA CLARTE DES INSTRUCTIONS.

NE PAS PROCEDER AU MONTAGE TANT QUE VOUS N'ETES PAS SUR QUE TOUTES LES PIECES SOIENT PRESENTES.

VEUILLEZ LIRE TOUTES LES INSTRUCTIONS AVANT DE CONTINUER.

## EN CAS DE DOUTE LORS DU MONTAGE DE NOS PRODUITS, CONSULTEZ UN DE NOS REVENDEURS OU FAITES APPEL A UN TECHNICIEN QUALIFIÉ.

VEUILLEZ NOTER QUE LA FAÇON DONT LE KIT EST EMBALLE NE REPRESENTE PAS NECESSAIREMENT LA MANIERE DE LE MONTER SUR LA MOTO.

SI DES RONDELLES EN CAOUTCHOUC SONT UTILISEES POUR MAINTENIR LES COMPOSANTS SUR LES BOULONS, ELLES PEUVENT ETRE JETEES.

#### **NOTICE DISPONIBLE AU TELECHARGEMENT SUR:**

WWW.RG-RACING.COM

R&G Racing

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 <a href="www.rg-racing.com">www.rg-racing.com</a> Email: <a href="mailto:info@rg-racing.com">info@rg-racing.com</a>




Page **5** of **6** BLGFK0038

OUTILS REQUIS	VALEURS DE SERRAGE
CLÉS ALLEN	M4 BOULON = 8Nm
	M5 BOULON = 12Nm
	M6 BOULON = 15Nm
	M8 BOULON = 20Nm
	M10 BOULON = 40Nm
	M12 BOULON = 40Nm

### **LÉGENDE**

ARTICLE NO.	DESCRIPTION	QTÉ
ARTICLE 1	M6 x 1 x 35.00mm BOULON	1
ARTICLE 2	PLG0005COMP PROTÈGE LEVIER MOULÉ	1
ARTICLE 3	M6x22mmØ RONDELLE PLATE	1
ARTICLE 4	M6x10mmØ RONDELLE PLATE	1
ARTICLE 5	NC0008 – M6 CAPUCHON D'ÉCROU	1

## **VUE D'ENSEMBLE**





Page 6 of 6 BLGFK0038

#### **NOTICE DE MONTAGE**

- Pour monter le protège levier (Article 2), retirez l'embout de guidon d'origine et rangez-le en toute sécurité.
- Insérez le boulon à tête cylindrique M6 (Article 1) à travers la rondelle plate M6 (Article 4), puis à travers le protège levier (Article 2).
- Placez la plus grande rondelle de 22 mm (article 3) à travers l'extrémité saillante du boulon.
- Placez cet assemblage sur la barre et serrez légèrement le boulon.
- Positionner de telle sorte que lorsque la moto est complètement verrouillée dans les deux sens, elle n'entre en contact avec aucune autre partie de la moto.
- Assurez-vous que les composants assemblés correspondent au schéma éclaté présenté à la page 2.
- Serrez complètement le boulon et vérifiez le fonctionnement de l'accélérateur, de la direction et du levier de frein avant de rouler.

ISSUE 1 - 15/09/2021 (TB)

IMPORTANT - LORS DE L'INSTALLATION DE CE PRODUIT, IL EST DE VOTRE RESPONSABILITÉ DE VOUS ASSURER QUE LE PRODUIT NE PUISSE EN AUCUN CAS ALTÉRER LE FONCTIONNEMENT DE LA MOTO ET DE VÉRIFIER RÉGULIÈREMENT LE SERRAGE ET LE BON FONCTIONNEMENT.

## NE PAS VÉRIFIER LES ÉLÉMENTS CI-DESSUS POURRAIT ENTRAÎNER DES BLESSURES OU DES DOMMAGES GRAVES.

#### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.