



FITTING INSTRUCTIONS FOR CR0046BK OFFSET COTTON REELS
HONDA CRF 250L 2013



THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED BELOW.
DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike
THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY)

**LEFT HAND
SIDE**





**RIGHT HAND
SIDE**



LEGEND

ITEM 1 = RIGHT AND LEFT HAND SIDE REPLACEMENT ADJUSTER BLOCKS/COTTON REEL MOUNTS (x2) (M0369).

ITEM 2 = COTTON REEL (B0443) FITTED WITH COMPRESION SLEEVE (CS303) (x2).

ITEM 3 = 10mm WASHERS 16mm OUTSIDE DIAMETER (x2).

ITEM 4 = M10x1.25x40mm LONG CAP HEAD BOLT (x2).

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

TOOLS REQUIRED

- 8mm A/F ALLEN KEY.
- 19 and 24mm A/F SOCKETS AND WRENCH.
- TORQUE WRENCH.

FITTING INSTRUCTIONS

Please read all instructions before commencing fitting

- Raise rear of bike suggest lifting from swing arm, support rear wheel (suggest using blocks of wood) to prevent wheel from dropping when rear spindle is removed.
- Undo the rear spindle nut.
- Remove the rear spindle and remove the OEM chain adjuster blocks.
- Place rear spindle through new adjuster block with the groove facing away from the wheel so the groove is visible on assembly.
- Slide spindle through swing arm, brake calliper and rear wheel ensuring new adjuster block sits in recess as original (shown above left).
- Fit the remaining new adjusting block over exposed end of spindle with the groove facing away from the wheel so the groove is visible on assembly as shown above right.
- Refit the spindle nut and tighten according to the manufactures instructions (88Nm) and check chain adjustment. Please note the new adjuster blocks have an engraved line to aid with adjustment.
- Fit the new cotton reels to the new adjuster blocks on both sides as shown above.
- Fit the bubble stickers to the new adjuster blocks on both sides as shown above.



ISSUE 1 02/08/2013 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



Instructions de montage pour CR0046BK Bobines de protection
HONDA CRF 250L 2013



Le kit contient les articles exposés ci-dessous, vérifier que toutes les pièces soient présentes avant de procéder au montage.

La façon dont le kit est emballé ne correspond pas forcément à la façon de monter les pièces sur la moto.

LES PIÈCES PRÉSENTÉES PEUVENT N'ÊTRE QUE REPRESENTATIVES, AFIN DE FACILITER ET CLARIFIER LES INSTRUCTIONS DE MONTAGE.

Coté gauche





Coté droit



LEGENDE

ARTICLE 1 = Blocks d'ajustement coté gauche et droit

Supports de bobines (x2) (M0369).

ARTICLE 2 = Bobine (B0443) avec manchon de compression (CS303) (x2).

ARTICLE 3 = 10mm Rondelles 16mm Diamètre extérieur (x2).

ARTICLE 4 = M10x1.25x40mm Boulon (x2).

NOTEZ QUE SI LES KITS SONT EMBALLES AVEC DES RONDELLES EN CAOUTCHOUC SERVANT A TENIR LES COMPOSANTS, CES RONDELLES DOIVENT ETRE JETTES.

TOOLS REQUIRED

- Clé Allen 8mm.
- Clé de 19 et 24mm.
- Clé dynamométrique.

INSTRUCTIONS DE MONTAGE :

Bien lire les instructions avant de commencer :

- Soulevez l'arrière de la moto, lever le bras oscillant, supporter la roue arrière (Nous vous suggérons d'utiliser des blocks de bois) pour éviter que la roue ne tombe lorsque l'axe arrière est enlevé.
- Enlever l'écrou d'axe arrière.
- Enlever l'axe arrière et enlever les blocs de réglage de la chaîne d'origine.
- Placer l'axe arrière à travers le nouveau bloc d'ajustement avec la face rainurée à l'écart de la roue de façon à ce que la rainure soit visible sur l'assemblage.
- Glisser l'axe à travers le bras oscillant, calé de frein et roue arrière en veillant à ce que le nouveau bloc d'ajustement se place dans le creux comme à l'origine (indiqué en haut à gauche).
- Poser le nouveau bloc d'ajustement autour de l'axe avec la face rainurée à l'écart de la roue de façon ce que la rainure soit visible sur l'assemblage (indiqué en haut à droite).

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



- Remettre l'écrou d'axe puis serrer selon les instructions de couple (88Nm) et vérifier l'ajustement de la chaîne. Notez que les nouveaux blocs de réglage disposent d'une ligne gravée pour simplifier l'ajustement.
- Monter les nouvelles bobines sur les nouveaux blocs de réglage des 2 cotés comme indiqué ci-dessus.
- Collez les stickers de caoutchouc to the new adjuster blocks on both sides as shown above.

ISSUE 1 02/08/2013 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.