



**Fitting Instructions for RAD0082BK Radiator Guard**  
**BMW F650GS '08-, F800R '09-, F800S, F800ST**



**In This Kit There Should Be**  
**1x Radiator Guard (RAD082BK)**  
**2x 100mm Lengths of self-adhesive Foam**  
**2x 200mm Cable Ties**



Picture 1



### **TOOLS REQUIRED**

- T25 Torx bit.

### **FITTING INSTRUCTIONS**

- To fit the radiator guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Remove the Torx 25 bolt from the bottom of the radiator.
- Offer the R&G Radiator Guard into position and using the cable ties supplied secure the guard using the two top tabs, as shown in picture 1.
- Refit the original Torx 25 bolt to secure the bottom of the radiator guard and tighten.

ISSUE 1 22/06/2012 (AR)

### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



**Instructions de montage pour RAD0082BK Protection radiateur  
BMW F650GS '08-, F800R '09-, F800S, F800ST**



**Le kit doit contenir**  
**1x Protection radiateur (RAD082BK)**  
**2x 100mm Longueurs de mousse autocollante**  
**2x 200mm Attaches câbles**



Photo 1



### Outils requis

- Torx T25.

### Instructions de montage

- Pour installer la grille de protection radiateur, couper la mousse autocollante en bandeaux de 10mm puis collez-les au bas du cadre de sorte à ce que les bandeaux se situent entre la grille de protection radiateur et le cadre.
- Enlever le boulon Torx T25 du bas du radiateur.
- Mettre la grille en position et utiliser les attaches cables fournis pour fixer la protection en utilisant les 2 languettes (photo 1).
- Remettre le boulon Torx 25 pour fixer le bas de la protection radiateur puis serrer.

ISSUE 1 22/06/2012 (AR)

### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)



**Montageanleitung für den RAD0082BK Kühlerschutz**  
**BMW F650GS '08-, F800R '09-, F800S, F800ST**



**Dieser Kit enthält:**  
**1x Kühlerschutz (RAD082BK)**  
**2x 200mm selbstklebende Schaumstoffstreifen**  
**2 x Kabelbinder**



Abbildung 1



**FOLGENDES WERKZEUG BENÖTIGEN SIE:**

- T25 Torx Schlüssel.

**MONTAGEANLEITUNG**

- Um den Kühlerschutz am Motorrad zu montieren, schneiden Sie zuerst die mitgelieferten Schaumstoff-Streifen in 10 mm breiten Streifen und kleben Sie diese auf der Rückseite des Kühlerschutzrahmens, so dass sie zwischen dem Kühlerschutz und dem Kühler angebracht sind.
- Entfernen Sie die Torx 25 Schraube vom Kühler unten.
- Den R&G Kühlerschutz in Position bringen und mit den mitgelieferten Kabelbinder befestigen – benutzen Sie hierbei die zwei Laschen oben, wie in Abbildung 1 abgebildet.
- Montieren und befestigen Sie die Original-Torx 25 Schraube wieder am Kühlerschutz unten.