



RAD0226

**Fitting Instructions for RAD0226 Radiator Guard**  
**YAMAHA MT-09 2017-/MT-09 TRACER 2015-/XSR900 2016-**

Page | 1



- In This Kit There Should Be**  
**1x Radiator Guard (RAD0226)**  
**1x S0722 Spacer**  
**1x M6x 35mm Long Button Head Bolt**  
**1x M6 Washer**  
**4x Cable Ties**  
**2x 100mm Lengths of self-adhesive Foam**




Picture 1




Picture 2



RAD0226




Picture 3



Picture 4



Picture 5



Picture 6



Picture 7



Picture 8



RAD0226

Page | 3

### **TOOLS REQUIRED**

- Socket set to include 3, 4 & 5mm A/F socket & wrench.
  - Cable Cutters

### **FITTING INSTRUCTIONS**

- To fit the radiator guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Remove the bolt that secures the top left of the radiator in place, as shown in picture 1.
- On the right side of the bike, the plastic bodywork around the air duct needs to be removed. To do this, remove the bolts as shown in picture 2, along with the two push rivets on the back side and gently pull away, as shown in picture 3.
- Now the top right mounting bolt can be removed, as shown in picture 4.
- With the bolt removed, replace with the top hat spacer provided in the kit. The smaller diameter end will fit in the rubber mount, as shown in picture 5.
- Offer the R&G Radiator Guard into place on the bike, ensuring that the brackets on the top of the radiator guard locate either side of the rubber mounts on the top of the radiator. On the right side, fit the M6 x 35mm long button head bolt provided through the radiator guard, spacer, rubber mount and tighten into the frame mount, as shown in picture 6.
- On the left side of the bike, the original OEM bolt can be refitted, first through the radiator guard then the rubber mount and into the frame mount, as shown in picture 7.
- Locate the cable tie through the two slots on the lower mount of the radiator guard and wrap around the lower radiator mount, before tightening, as shown in picture 8.
- Ensure the radiator guard is correctly mounted and tighten all bolts evenly.
- Re-fit the two push rivets and bolt that secure the right side air duct in place.

ISSUE 1 17/04/2018 (NSY)

### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)



RAD0226

**NOTICE DE MONTAGE POUR RAD0226 GRILLE DE PROTECTION**  
**YAMAHA MT-09 2017-/MT-09 TRACER 2015-/XSR900 2016-**

Page | 4



**Le kit doit contenir :**

- 1x Grille de protection (RAD0226)
- 1x S0722 Entretoise
- 1x Boulon M6x 35mm
- 1x M6 Rondelle
- 4x Collier de serrage
- 2x 100mm Longueurs de mousse autocollante



RAD0226



Photo 1



Photo 2




Photo 3



Photo 4




Photo 5



Photo 6



RAD0226

Page | 6



Photo 7



Photo 8

#### **OUTILS REQUIS**

- Jeu de clés 3, 4, et 5mm
  - Coupe câble

#### **Instructions de montage :**

- Couper la mousse en bandeaux de 10mm puis collez ces bandeaux au bas du support de protection radiateur, de façon à ce que ces bandeaux se situent entre la protection radiateur et le radiateur.
- Enlever le boulon qui fixe le côté gauche supérieur du radiateur en place (Photo 1).
- Du côté droit de la moto, le carénage en plastic autour du conduit d'air doit être enlevé. Pour cela, enlever les boulons (Photo 2), avec les 2 rivets poussoirs au bas, puis tirez doucement (Photo 3).
- A présent le boulon de fixation en haut à droite peut être enlevé (Photo 4).
- Une fois le boulon enlevé, remplacez-le par l'entretoise du haut fournie dans le kit. L'extrémité avec le plus petit diamètre va dans le support en caoutchouc (Photo 5).
- Mettre la grille de protection R&G en place sur la moto, en veillant à ce que les supports du haut de la grille de protection soient placés dans les supports en caoutchouc sur le haut du radiateur. Du côté droit, passer le boulon M6 x 35mm fourni à travers la grille de protection radiateur, l'entretoise, le support en caoutchouc, puis serrer dans le support cadre (Photo 6).
- Du côté gauche de la moto, le boulon d'origine peut à présent être remis, d'abord à travers la grille de protection radiateur, puis le support en caoutchouc et enfin dans le support cadre (Photo 7).
- Passer le collier de serrage à travers les 2 fentes sur le support inférieur de la grille de protection radiateur puis encercler le support radiateur inférieur, avant de serrer (Photo 8).
- Veillez à ce que la grille de protection radiateur soit correctement montée puis serrer tous les boulons de façon égale.
- Remettre les 2 rivets poussoirs et le boulon qui fixe le côté droit du conduit d'air en place.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)



RAD0226

ISSUE 1 17/04/2018 (NSY)

#### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)



RAD0226

**Montageanleitung für RAD0226 Kühlerschutz**  
**YAMAHA MT-09 2017-/MT-09 TRACER 2015-/XSR900 2016-**

Page | 8



- Dieser Kit beinhaltet:**  
1x Kühlerschutz (RAD0226)  
1x S0722 Distanzhalter  
1x M6x 35mm Inbusschraube  
1x M6 Unterlegscheibe  
4x Kabelbinder

**2x 100mm selbstklebende Schaumstoffstreifen**



Abbildung 1



Abbildung 2

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)





RAD0226




Abbildung 3



Abbildung 4



Abbildung 5



Abbildung 6



Abbildung 7



Abbildung 8



RAD0226

### **SIE BENÖTIGEN FOLGENDES WERKZEUG:**

- Steckschlüsselsatz mit 3, 4 & 5mm Steckschlüsseln
- Seitenschneider

Page | 10

### **MONTAGEANLEITUNG**

- Um den Kühlerschutz am Motorrad zu montieren, schneiden Sie zuerst die mitgelieferten Schaumstoffstreifen in 10 mm breite Streifen und kleben Sie diese auf der Rückseite des Kühlerschutzrahmens, so dass sie zwischen dem Kühlerschutz und dem Kühler angebracht sind.
- Entfernen Sie die Schraube, die den Kühler oben links in Position befestigt – siehe Abbildung 1.
- An der rechten Seite des Motorrades muss die Kunststoffverkleidung um den Lufteinlass entfernt werden. Entfernen Sie die Schrauben, die in Abbildung 2 abgebildet sind, sowie die zwei Nieten an der Rückseite und vorsichtig wegziehen – siehe Abbildung 3.
- Nun kann die Montageschraube oben rechts entfernt werden, wie in Abbildung 4 abgebildet.
- Wenn die Schraube entfernt ist, ersetzen Sie sie mit dem Distanzhalter vom Kit. Das Ende mit dem kleinen Durchmesser passt in die Gummihalterung – siehe Abbildung 5.
- Den R&G Kühlerschutz am Motorrad positionieren – bitte darauf achten, dass die Halterungen, oben auf dem Kühlerschutz auf beiden Seiten der Gummihalterungen oben am Kühler positioniert sind. An der rechten Seite die M6 x 35mm Inbusschraube vom Kit durch den Kühlerschutz, den Distanzhalter und die Gummihalterung führen und anschließend in der Rahmenhalterung befestigen – siehe Abbildung 6.
- An der linken Seite des Motorrades kann nun die original Schraube wieder montiert werden – zuerst durch den Kühlerschutz, dann durch die Gummihalterung und anschließend in der Rahmenhalterung befestigen – siehe Abbildung 7.
- Den Kabelbinder durch die zwei Schlitze an der unteren Halterung fädeln und um die untere Kühlerhalterung wickeln, bevor Sie sie befestigen – siehe Abbildung 8.
- Überprüfen Sie, dass der Kühlerschutz sicher montiert ist und alle Schrauben gleichmäßig festgezogen sind.
- Montieren Sie die zwei Nieten wieder, die den Lufteinlass für die rechte Seite befestigen.

AUSGABE 1 17/04/2018 (NSY)

#### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and d

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)