




Fitting Instructions for SRG0043SS Radiator Guard
BMW R1200 R & R1200RS '15-



In This Kit There Should Be
1x Stainless Radiator Guard (SRG0043)
1x Cable Tie
2x 100mm Lengths of self-adhesive Foam



Picture 1



Picture 2

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ


Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Picture 3



Picture 4



Picture 5



Picture 6

GENERAL TORQUE SETTINGS

M4 BOLT = 8Nm

M5 BOLT = 12Nm

M6 BOLT = 15Nm

M8 BOLT = 20Nm

M10 BOLT = 40Nm

M12 NYLOC NUT = 40Nm



TOOLS REQUIRED

- Socket set to include Torx bits & wrench.
 - Cable Cutters

FITTING INSTRUCTIONS

- To fit the stainless radiator guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Remove the two Torx bolt that secure the bottom of the plastic guard in place, as arrowed in picture 1.
- Remove the Torx bolt that is at the top of the radiator, as shown in picture 2.
- Offer the R&G Stainless Radiator Guard in place by pulling the bottom of the OEM guard outward and sliding the radiator guard up between this and the radiator, as shown in picture 3.
- Locate the bottom mounts of the radiator guard over the mounting holes on the radiator and then re-position the OEM plastic guard into place. With the holes no aligned, refit the original Torx bolts and loosely tighten, as shown in picture 4.
- Loop the cable tie through the two slots on the top right of the radiator and around the plastic “T” shaped mount on the radiator, as shown in picture 5, before loosely tightening.
- Re-fit the original bolt through the top left mount on the radiator guard and into the threaded boss on the radiator.
- With the radiator guard correctly fitted, as shown in picture 6, tighten all the bolts evenly along with the cable tie.

ISSUE 1 13/10/2015 (AR)

Digital copies of these instructions are available to download from www.rg-racing.com

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Instructions de montage pour SRG0043SS Protection radiateur
BMW R1200 R & R1200RS '15-



Le kit doit contenir :

- 1x Protection radiateur (SRG0043)
- 1x Collier de serrage
- 2x 100mm Longueurs de mousses autocollantes



Photo 1



Photo 2

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Photo 3



Photo 4




Photo 5



Photo 6

COUPLES DE SERRAGE RECOMMANDÉS :

- M4 BOULON = 8Nm
- M5 BOULON = 12Nm
- M6 BOULON = 15Nm
- M8 BOULON = 20Nm
- M10 BOULON = 40Nm
- M12 ECROU = 40Nm



Outils requis

- Clé Torx.
- Pince coupante

INSTRUCTIONS DE MONTAGE

- Couper la mousse en bandeaux de 10mm puis collez ces bandeaux au bas du support de protection radiateur, de façon à ce que ces bandeaux se situent entre la protection radiateur et le radiateur.
- Enlever les 2 boulons Torx qui fixent le bas de la grille plastique en place, voir photo 1.
- Enlever le boulon Torx situé sur le haut du radiateur, voir photo 2.
- Mettre la grille R&G en place en tirant le bas de la protection d'origine vers l'extérieur et en glissant la protection radiateur vers le haut, voir photo 3.
- Placer les supports inférieurs de la protection radiateur sur les trous de fixation sur le radiateur puis repositionnez la grille plastique d'origine en place. Avec les trous non alignés, replacez les boulons Torx d'origine puis serrer doucement, voir photo 4.
- Passez les colliers dans les 2 fentes en haut à droit du radiateur puis autour du support T en plastique du radiateur, voir photo 5, avant de serrer légèrement.
- Réinsérer le boulon d'origine dans le support supérieur gauche de la protection radiateur puis dans le patron fileté du radiateur.
- Une fois la grille correctement installée, selon le résultat présenté sur la photo 6, serrer tous les boulons de façon identique, en utilisant également un collier de serrage.

ISSUE 1 13/10/2015 (AR)

Ces instructions de montage sont disponibles sur www.rg-racing.com

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com