



Fitting Instructions for OCG0012BK Oil Cooler Guard
APRILIA RSV-4/TUONO V4 2011-



In This Kit There Should Be

- 1x Oil Cooler Guard (OCG0012).
- 2x 100mm Lengths of self-adhesive Foam.
- 2x M5x20mm long button head bolts.
 - 2x M5 washers.



- Remove the two upper bolts and single lower in positions arrowed at top of above picture.
- Remove the original plastic oil cooler cover.
- To fit the oil cooler guard to the bike cut the foam strips provided into 10mm wide pieces and stick them to the back of the oil cooler guard, so that they sit between the oil cooler guard and the oil cooler itself.
- Fit the oil cooler guard as shown above and secure using the single original lower bolt.
- Refit the original plastic oil cooler cover and using the two new bolts and washers from kit secure the new oil cooler guard and original oil cooler cover as shown in top picture.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have



been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

Issue 1 09/08/2011 (NSY)



FRANCE
Instructions de montage de la protection de radiateur d'huile
OCG0012BK
APRILIA RSV-4/TUONO V4 2011-

Ce kit comprend:
1x protection (OCG0012).
2x bande de mousse adhésive 100 mm.
2x vis M5 x 20 mm
2x Rondelles M5.

- Enlever les vis de fixation qui retiennent le radiateur (voir photo) 2 vis en haut et 1 vis en bas.
- Enlever le cache du radiateur en plastique.
- Pour fixer la protection de radiateur d'huile sur la moto, vous devrez couper et coller des morceaux de 10 mm de mousse au dos de la protection. Ces morceaux de mousse se positionneront entre la protection et le radiateur.
- Placer et fixer la protection de radiateur sur le radiateur d'huile, utilisez la vis d'origine inférieure pour fixer la fixation basse.
- Replacer le cache en plastique précédemment retiré.
Fixer ensuite les fixations supérieures à l'aide des vis et rondelles livrées dans le kit. (voir la photo).

