



**FITTING INSTRUCTIONS FOR ECC0129 LHS ENGINE CASE COVER  
HONDA CBR 900RR 2000-'03**



In this kit there should be:  
1 x Engine Case Cover (ECC0129)  
3 x M6x38mm long button head bolts  
2 x M6 Washers

**PLEASE READ THESE INSTRUCTIONS FULLY BEFORE STARTING**

- Remove the lower fairing.
- Remove the left-hand side fairing.
- Please make sure the engine is cold before proceeding with the fitting of the R&G cover.
- Remove the three engine case bolts arrowed above. Hold the cover loosely over the case to help identify the correct ones. **DO NOT REMOVE ALL OF THE CASE BOLTS.**
- Offer up the R&G cover to the engine and carefully fit it over the engine casing. Ensure that the three R&G bolts are lined up with the holes in the engine casing, and then push on as far as it will go.
- PLEASE NOTE – The bolts marked with a star on the diagram require washers.
- With a 4mm Allen key tighten the bolts equally so that they pull the cover into place. **DO NOT FULLY TIGHTEN.**
- Finally use a torque wrench set at 10 nm (7 Lb ft) to fully tighten.
- Refit the lower and side fairings.
- It is suggested that you check the tightness of the mounting bolts on a regular basis i.e. when cleaning or once a month.
- NOTE for the cleaning of this product you should only use a soft polishing cloth and a mild general cleaning agent



- AVOID HARMFUL CHEMICALS IF IN DOUBT DO NOT USE AS THEY COULD ALTER THE STRENGTH OF THE COVER.
- R&G will accept no liability if the above procedure and torque settings are not followed.



**Instructions de montage pour ECC0129 coté gauche**  
**Protection carter moteur**  
**HONDA CBR 900RR 2000-'03**



Le kit doit contenir:

- 1 x Protection carter moteur (ECC0129)
- 3 x M6x38mm Long boulon à tête ronde
  - 2 x M6 Washers

**BIEN LIRE LES INSTRUCTIONS AVANT DE COMMENCER**

- Enlever le carénage inférieur.
- Enlever le carénage coté gauche
- S'assurer que le moteur soit froid avant de procéder au montage.
- Enlever les 3 boulons de carter moteur indiqués ci dessus. Tenir la protection afin d'aider à identifier les bons trous. **NE PAS ENLEVER LES BOULONS DE CARTER MOTEUR.**
- Poser la protection R&G sur le carter moteur et l'installer. S'assurer que les 3 boulons R&G soient bien alignés avec les trous dans le carter moteur, puis enfoncer.
- NOTE – Les boulons marqués par une étoile sur le schéma requièrent des rondelles.
- Serrer les boulons avec une clé Allen de 4mm de façon égale pour que la protection se mette en place. **NE PAS SERRER COMPLETEMENT.**
- Utiliser une clé dynamométrique à 10 Nm (7 Lb ft) pour bloquer.
- Réinstaller les carénages.
- Nous vous suggérons de vérifier le serrage au moins une fois par mois, lors du nettoyage par exemple.



- NOTE: Pour le nettoyage, vous devriez utiliser uniquement un chiffon doux et un agent nettoyant doux.
- Ne pas utiliser d'agents chimiques qui pourraient altérer l'efficacité de la protection.
- R&G n'acceptera aucune responsabilité en cas de mauvais couple de serrage ou d'utilisation inappropriée d'agents nocifs.

ISSUE 1 14/05/2012 (NSY)

**CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

**R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.