

# FITTING INSTRUCTIONS FOR CP0100 CRASH PROTECTORS KAWASAKI ZZR 600 D/E

## Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away*!

#### Offside (right side as you sit on the bike)

- Remove lower fairing panel (belly pan).
- Undo engine bolt.
- Wind bolt out until it touches inside of fairing and paint end.
- Refit the panel, therefore marking the inside of the fairing panel with the paint.
- Remove the fairing, and, using a 28 mm tank cutter/cone cutter, drill the panel at the paint mark using the
  pilot drill.
- Offer the panel back up to ensure you are in the correct position.
- Turn the fairing over and support it, enter the pilot drill into the hole (from the outside) and carefully cut the 28-mm dia hole.
- Replace the fairing.
- Take the longer of the two bolts supplied, slide the washer supplied over the bolt, and slide the bobbin supplied over the bolt.
- Take the longer of the two spacers, slide over the bolt and up behind the bobbin. Pass the assembly through the drilled hole and tighten until you feel some compression from inside the protector. Then turn as you feel compression increase and resistance is met. Then give a quarter turn. Do not overtighten and do not exceed 38nm of torque.

# Nearside

Repeat as above, except using the shorter spacer and shorter bolt.

Due to the risk of cross threading of bolts etc; we always recommend that our products be fitted by one of our official dealers or a qualified mechanic.

# CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes.

Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products.

On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned.

These terms do not affect the Buyer's statutory rights.

### R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected)

Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor.

Goods must be in re-sellable condition, in the opinion of R&G Racing.

All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase).

The customer must pay any and all carriage charges.

No returns of discontinued products, unless within 14 days of purchase.

This policy does not affect your statutory rights and does not refer to faulty goods.

#### **R&G** Racing