



## FITTING INSTRUCTIONS FOR CP0180BL CRASH PROTECTORS KAWASAKI GPZ 500

**Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike**

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

- Undo nut on front engine bolt (the one that goes right through the engine)
- Take the R&G replacement engine bar and, using a soft hammer, knock out the oem bolt leaving it with equal amounts protruding from either side of the frame
- Fit the stainless steel extensions to each end of the replacement engine bar and tighten. Note the smaller diameter goes against the frame
- Take one of the 10mm bolts and slide one of the 10mm washers up to the head of the bolt, followed by the smaller of the two aluminium spacers
- Take one of the bobbins and pass the bolt through
- Screw the assembly in to the left side (as you sit on bike) extension and tighten bolt until you feel some compression from inside the protector. Turn a little more so that you feel the compression increase slightly. Then apply a quarter turn. Do not overtighten as damage can occur to the bike. Do not exceed 40nm of torque.
- Repeat this procedure for the right hand side, only the aluminium spacer goes between the bobbin and the extension

Due to the risk of cross-threading, overtightening etc. we always recommend that our kits be fitted by one of our official dealers or at least a qualified mechanic

### CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order.  
The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes.  
Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products.  
On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.  
Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned.  
These terms do not affect the Buyer's statutory rights.

### R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected)  
Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor.  
Goods must be in re-sellable condition, in the opinion of R&G Racing.  
All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase).  
The customer must pay any and all carriage charges.  
No returns of discontinued products, unless within 14 days of purchase.  
This policy does not affect your statutory rights and does not refer to faulty goods.